

Ambient Vaporizer 20ft.

The PRS ambient vaporizer is an uncomplicated heat exchanger which vaporizes liquid nitrogen into ambient temperature gas by using the heat absorbed from ambient air. Due to this simple principle of operation these vaporizers do not require external power.

Liquid nitrogen passes through the interconnected tubes in various series and parallel paths, so it comes out as a gas. The ambient vaporizer can also be used for gas-up of Ethylene and Propylene pipelines.

Also a combination of two separate vaporizer units and one 20.000ltr high pressure liquid Nitrogen tank is possible. The units are installed on a trailer using the container lock system which makes it easy to be disassembled.

Capacity of two (2) ambient air vaporizer unit for Nitrogen

1.300 Nm3/hr (46.000 scf/Hr) @ ambient temperature Maximum working pressure 40 bar (1.450 Psi)

Dimensions (overall)

2 x 10ft Container Dimension

Length:	2990 mm
Width:	2440 mm
Height:	2590 mm
Weight:	1.500 KG

Connections

Inlet 1.5" NIT 150 Outlet 1-1/2" 600# RF flanged

Typical applications:

- Nitrogen purging
- Nitrogen back up
- Helium Leaktesting
- Pipeline pigging

Other applications

INTERNATIONAL Pipeline Refinery Services AV-01 Vaporizing LNG, Ethylene, Propylene and other natural gasses.

24/7 excelling in services!

PRS International Industrieweg 10 7761 PV Schoonebeek The Netherlands

T: +31 (0)524 599 980 E: info@prs-international.nl W: www.prs-international.nl

a VolkerWessels company